



四列圆锥滚子轴承

Four-Row Taper Roller Bearings



该种轴承有四列滚子，可以承受很大的径向负荷，并可承受两个方向的轴向负荷。可限制轴或外壳两个轴向方向位移在轴承的轴向游隙范围内。

该种轴承成套供应，新轴承游隙出厂前已调好，安装时应特别注意外圈、两内圈、两外隔圈、一内隔圈的打字编号，相同编号的端面相对接触安装。

改变隔圈的宽度尺寸，可调整轴承的轴向游隙。


Four Row Taper Roller Bearings

This type of bearing has four rows of taper rollers, it is used to bear heavier radial load and axial load in double direction also, it can limit the displacement of axis or housing in the dimension of axial clearance.

The bearing is provided in sets. The clearance of new bearing has been adjusted well before being out of our company. Please notice the words and numbers on outer ring, two inner rings, two rings between outer rings and one ring between inner rings, the end planes of the same number should be in contact in position when mount the bearing.

Changing the height of the ring between one inner(outer)ring and the other, we'll adjust the axial clearance of bearings.

四列圆锥滚子轴承



轴承型号 Bearing Designations		主要尺寸 Principal Dimensions (mm)				额定负荷 Rated Loads (kN)		极限转速 Limiting Speed (r/min)		重量 Weight
旧型号 OLD	新型号 NEW	d	D	B	r _(min)	动负荷 Dynamic C _r	静负荷 Static C _{0r}	脂 Grease	油 Oil	kg
2077930	382930	150	210	165	3	602	1580	800	1000	21.2
	382034	170	260	230	3	1270	3290	670	850	39.5
	382040	200	310	275	3	1760	4200	560	700	75.1
2077144	382044	220	340	305	3	2070	5430	500	630	91
2077148	382048	240	360	310	3.5	2110	5610	450	560	98
	382952	260	360	265	3.5	1760	5220	450	560	76.3
	382052	260	400	345	3.5	2710	7140	430	530	153
	381156	280	460	324	3.5	2840	7290	360	450	200
	382960	300	420	300	4	2330	7210	380	480	130
	382060	300	460	390	4	3180	9330	360	450	219
2077160	381160	300	500	370	4	3390	8710	340	430	285
	382064	320	480	390	4	3180	9330	340	430	234
2077164	382968	340	460	310	4	2480	8100	340	430	145
	381068	340	520	325	5	3100	8620	320	400	234
	381168	340	580	425	5	4580	11700	280	360	441
	381072	360	540	325	5	3360	8840	300	380	248
	381076	380	560	325	5	3360	8840	280	380	281
	381176	380	620	420	5	4710	12300	240	360	487
1077776	381080	400	600	356	5	4160	10400	240	320	317
	381184	420	620	356	5	4160	10400	220	300	358
	381184	420	700	480	5	6780	18500	190	260	760
	381088	440	650	376	5	4290	12390	200	280	401
1077992	381992	460	620	310	6	3360	10200	200	280	173
1077996	381996	480	650	338	6	3390	10500	190	260	301